Reassign the Com port assigned to COM1 or COM2 for USB Option D24 Encoder

-The VCM driver must be installed first before any further procedures (make sure it's plugged into a free USB port).

- Go to start menu and click on your Control Panel
- Once you're in the <u>Control Panel</u> window, click on the <u>System</u> icon.
- Click on the <u>Hardware</u> tab, and another click on <u>Device Manager</u>, under Ports (COM & LPT), right click on <u>USB Serial Port</u>

Device Manager	🔄 🗖 🔀 System Properties
le Action View Help	System Restore Automatic Updates R
⊢→ 🔟 🗳 😫 💐 📚 🗸	General Computer Name Hardware Ac
SUPPORT Computer Disk drives Display adapters DVD/CD-ROM drives Floppy disk controllers Floppy disk drives Disk drives Display adapters Floppy disk controllers Floppy disk drives Display adapters Display adapters Floppy disk drives Display adapters Display adapters Display adapters Display disk drives Display adapters Display adapters Modems Monitors Modems Ports (COM & LPT) Ports (COM & LPT) Display adapters Ports (COM & LPT) Display adapters Ports (COM & LPT) Display adapters Processors Sound, video and game controllers System devices	Device Manager Image: Image: <t< th=""></t<>

- On <u>Port Settings</u> tab, click <u>Advance...</u>
- Change the COM Port number to: <u>COM2</u> or <u>COM1</u> (depending on computer). Then, click <u>OK</u>

Advanced Settings for COM4		? 🛛	
COM Port Number: COM2 USB Transfer Sizes Select lower settings to correct performance problems at low I Select higher settings for faster performance. Receive (Bytes): 4096 Transmit (Bytes): 4096	baud rates.	OK Cancel Defaults	•
BM Options Select lower settings to correct response problems. Latency Timer (msec): 16 Timeouts Minimum Read Timeout (msec): 0 Minimum Write Timeout (msec): 0	Miscellaneous Options Serial Enumerator Serial Printer Cancel If Power Off Event On Surprise Removal Set RTS On Close Disable Modem Ctrl At Startup		

• Once COM Port is changed verify by checking the port settings tab again



Go to Encoder Utility Software.

• Click on <u>Com Setting.</u> In <u>COM Port Configuration</u> window, adjust the right COM selection. Then, click <u>OK</u>

Com Port C	onfiguration	
	C Com1 C Com2	
Baudrate	9600 💌	
	ОК	

After procedure, Click \underline{Get}

Card Reader Utility (Version 1.9)			
m Setting			
HID Mifare Controller IClass			
9600 Set Baudrate	Firmware Version	Get	
Set Boot Mode			

For More Information Please Contact <u>support@digion24.com</u> 805-584-9884